

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An apparatus, comprising:

a memory device; and

a processor disposed in communication with the memory device, the processor configured to:

conduct an inquiry to discover ~~at least one~~ nearby devices;

determining, whether a discovered nearby device provides an indication that it may include a middleware software, the middleware software configured for providing application and service discovery;

when the discovered nearby device does not provide an indication that it may include the middleware software;

disconnect communication session establishment with the discovered nearby device;

when the discovered nearby device provides ~~an inquiry result includes~~ an indication that ~~it at least one nearby device~~ may include a the middleware layer software, ~~the middleware layer comprising a middleware software for providing application and service discovery;~~

create a wireless short-range communication connection to ~~said at least one the discovered~~ nearby device;

confirm whether said ~~at least one~~ nearby device includes the middleware layer software by requesting corresponding information from said ~~at least one~~ nearby device via the wireless short-range communication connection; and

when said ~~at least one~~ nearby device includes the middleware layer software:

execute the middleware layer software to perform application and service discovery with said nearby device.

2. (Previously Presented)      The Apparatus of claim 1, wherein the middleware layer includes a

service discovery protocol and at least one computer program, each computer program comprising at least one sequence of operational instructions.

3. (Previously Presented)      The Apparatus of claim 1, wherein when said at least one nearby device includes the middleware layer, the processor is further configured to:  
execute the middleware layer to launch applications and services.

4.      (Previously Presented)      The Apparatus of claim 1, wherein to conduct the inquiry, the processor is further configured to:  
send an inquiry request message;  
receive an inquiry response message from said at least one nearby device, the inquiry response message including the indication.

5.      (Previously Presented)      The Apparatus of claim 4, wherein the inquiry request message is a Bluetooth inquiry command, and the inquiry response message is a Bluetooth inquiry result command.

6.      (Previously Presented)      The Apparatus of claim 5, wherein setting at least one bit in the Bluetooth inquiry result command to at least one predetermined value is the indication.

7.      (Previously Presented )      The Apparatus of claim 6, wherein said at least one bit includes at least one of the ad hoc networking aware bit, the location information bit, or the telephony capable bit.

8.      (Previously Presented)      The Apparatus of claim 5, wherein setting at least two bits in the Bluetooth inquiry result command to at least one predetermined value is the indication.

9.      (Previously Presented )      The Apparatus of claim 8, wherein said at least two bits includes at least two of the ad hoc networking aware bit, the location information bit, or the telephony capable bit.

10. (Previously Presented ) The Apparatus of claim 8, wherein said at least two bits includes the ad hoc networking aware bit, and at least one of the location information bit, or the telephony capable bit.
11. (Previously Presented) The Apparatus of claim 1, wherein to create the connection, the processor is further configured to:  
send a paging request message directed to said at least one nearby device; and  
receive a paging accept message from said at least one nearby device.
12. (Previously Presented) The Apparatus of claim 1, wherein to confirm that said at least one nearby device includes the middleware layer, the processor is further configured to:  
send a recognition request message to said at least one nearby device; and  
receive a recognition response message from said at least one nearby device.
13. (Previously Presented) The Apparatus of claim 12, wherein receipt of the recognition response message confirms that said at least one nearby device includes the middleware layer.
14. (Previously Presented) The Apparatus of claim 12, wherein the recognition response message includes a confirmation that said at least one nearby device includes the middleware layer.
15. (Previously Presented) The Apparatus of claim 14, wherein setting at least one bit in the recognition response message to at least one predetermined value is the confirmation.
16. (Previously Presented) The Apparatus of claim 12, wherein the recognition request message is a Bluetooth Service Discovery Protocol request and the recognition response message is a Bluetooth Service Discovery Protocol response.
17. (Previously Presented) The Apparatus of claim 1, wherein to execute the middleware layer

to perform application and service discovery, the processor is further configured to:

receive a notification message from said at least one nearby device, the notification message including a local application directory stored in said at least one nearby device;  
store an update to a combined application directory, the update based on a comparison of the local application directory and the combined application directory; and  
send an update message to said at least one nearby device, the update message including an update portion of the combined application directory for updating the local application directory stored in said at least one nearby device.

18. (Previously Presented) The Apparatus of claim 17, wherein the processor is further configured to:

launch a local application based on a reference in the combined application directory; and  
connect the local application to a counterpart application executing on said at least one nearby device.

19. (Currently Amended) A method for performing device detection and service discovery in a mobile ad hoc communications network, comprising:

conducting an inquiry to discover ~~at least one~~ nearby devices,  
determining, whether a discovered nearby device provides an indication that it may include a middleware software, the middleware software configured for providing application and service discovery;

when the discovered nearby device does not provide an indication that it may include the middleware software;

disconnect communication session establishment with the discovered nearby device;

when the discovered nearby device provides an inquiry request result includes an indication that it ~~at least one nearby device~~ may include a the middleware layer software, ~~the middleware layer comprising a middleware software for providing application and service discovery;~~

creating a wireless short-range communication connection to said ~~at least one~~ discovered

nearby device;  
confirming whether said ~~at least one~~ nearby device includes the middleware layer software  
by requesting corresponding information from said ~~at least one~~ nearby device via the  
wireless short-range communication connection;  
and  
when said ~~at least one~~ nearby device includes the middleware layer software:  
executing the middleware layer software to perform application and service  
discovery with said nearby device.

20. (Original) The method of claim 19, wherein the middleware layer includes a service discovery protocol and at least one computer program, each computer program comprising at least one sequence of operational instructions.
21. (Original) The method of claim 19, wherein when said at least one nearby device includes the middleware layer, the method further comprises:  
executing the middleware layer to launch applications and services.
22. (Previously Presented) The method of claim 19, wherein the conducting of the inquiry further comprises:  
sending an inquiry request message; and  
receiving an inquiry response message from said at least one nearby device, the inquiry response message including the indication.
23. (Original) The method of claim 22, wherein the inquiry request message is a Bluetooth inquiry command, and the inquiry response message is a Bluetooth inquiry result command.
24. (Original) The method of claim 23, wherein setting at least one bit in the Bluetooth inquiry result command to at least one predetermined value is the indication.
25. (Original) The method of claim 24, wherein said at least one bit includes at least one of the

ad hoc networking aware bit, the location information bit, or the telephony capable bit.

26. (Original) The method of claim 23, wherein setting at least two bits in the Bluetooth inquiry result command to at least one predetermined value is the indication.

27. (Original) The method of claim 26, wherein said at least two bits includes at least two of the ad hoc networking aware bit, the location information bit, or the telephony capable bit.

28. (Original) The method of claim 26, wherein said at least two bits includes the ad hoc networking aware bit, and at least one of the location information bit, or the telephony capable bit.

29. (Previously Presented) The method of claim 19, wherein the creating of the wireless short-range connection further comprises:

    sending a paging request message to said at least one nearby device; and  
    receiving a paging accept message from said at least one nearby device.

30. (Original) The method of claim 19, wherein the confirming further comprises:  
    sending a recognition request message to said at least one nearby device; and  
    receiving a recognition response message from said at least one nearby device,

31. (Original) The method of claim 30, wherein the receiving of the recognition response message confirms that said at least one nearby device includes the middleware layer.

32. (Original) The method of claim 30, wherein the recognition response message includes a confirmation that said at least one nearby device includes the middleware layer.

33. (Original) The method of claim 32, wherein setting at least one bit in the recognition response message to at least one predetermined value is the confirmation.

34. (Original) The method of claim 30, wherein the recognition request message is a

Bluetooth Service Discovery Protocol request and the recognition response message is a Bluetooth Service Discovery Protocol response.

35. (Original) The method of claim 19, wherein the executing of the middleware layer to perform application and service discovery further comprises:

receiving a notification message from said at least one nearby device, the notification message including a local application directory stored in said at least one nearby device;

storing an update to a combined application directory, the update based on a comparison of the local application directory and the combined application directory; and

sending an update message to said at least one nearby device, the update message including an update portion of the combined application directory for updating the local application directory stored in said at least one nearby device.

36. (Original) The method of claim 35, further comprising:

launching a local application based on a reference in the combined application directory;  
and

connecting the local application to a counterpart application executing on said at least one nearby device.

37. (Currently Amended) A computer program product, executable in a computer system, comprising:

a computer recordable and readable medium storing:

program code for conducting an inquiry to discover ~~at least one~~ nearby devices;

program code for determining, whether a discovered nearby device provides an indication that it may include a middleware software, the middleware software configured for providing application and service discovery;

when the discovered nearby device does not provide an indication that it may include the middleware software;

disconnect communication session establishment with the discovered nearby

device;

~~program code for creating a wireless short-range connection to said at least one nearby device when the discovered nearby device provides an inquiry result includes an indication that it at least one nearby device may include a middleware layer software, the middleware layer comprising a middleware software for providing application and service discovery creating a wireless short-range communication connection to the discovered nearby device;~~

~~program code for confirming whether said at least one nearby device includes the middleware layer software by requesting corresponding information from said at least one nearby device via the wireless short-range communication connection when the inquiry includes the indication that said at least one nearby device may includes the middleware layer software; and~~

~~program code for executing the middleware layer software to perform application and service discovery with said nearby device when said at least one nearby device includes the middleware layer.~~

38. (Original) The computer program product of claim 37, wherein the middleware layer includes a service discovery protocol and at least one computer program, each computer program comprising at least one sequence of operational instructions.

39. (Original) The computer program product of claim 37, the computer recordable and readable medium further storing:

program code for executing the middleware layer to launch applications and services when said at least one nearby device includes the middleware layer.

40. (Previously Presented) The computer program product of claim 37, wherein the program code for conducting the inquiry further comprises:

program code for sending an inquiry request message; and

program code for receiving an inquiry response message from said at least one nearby device, the inquiry response message including the indication.



41. (Previously Presented) The computer program product of claim 37, wherein the program code for creating the wireless short-range connection further comprises:
- program code for sending a paging request message directed to said at least one nearby device; and
  - program code for receiving a paging accept message from said at least one nearby device.
42. (Original) The computer program product of claim 37, wherein the program code for confirming that said at least one nearby device includes the middleware layer further comprises:
- program code for sending a recognition request message to said at least one nearby device;
  - and
  - program code for receiving a recognition response message from said at least one nearby device,
43. (Original) The computer program product of claim 37, wherein the program code for executing the middleware layer to perform application and service discovery further comprises:
- program code for receiving a notification message from said at least one nearby device, the notification message including a local application directory stored in said at least one nearby device;
  - program code for storing an update to a combined application directory, the update based on a comparison of the local application directory and the combined application directory; and
  - program code for sending an update message to said at least one nearby device, the update message including an update portion of the combined application directory for updating the local application directory stored in said at least one nearby device.
44. (Original) The computer program product of claim 43, wherein the program code for executing the middleware layer to perform application and service discovery further comprises:
- program code for launching a local application based on a reference in the combined application directory; and

program code for connecting the local application to a counterpart application executing on said at least one nearby device.

45. (Currently Amended) Apparatus, comprising:  
means for conducting an inquiry to discover ~~at least one~~ nearby devices,  
means for determining, whether a discovered nearby device provides an indication that it may include a middleware software, the middleware software configured for providing application and service discovery;  
when the discovered nearby device does not provide an indication that it may include the middleware software:  
disconnect communication session establishment with the discovered nearby device;  
when the discovered nearby device provides an indication that it may include the middleware software layer  
  
means for creating a wireless short-range communication connection to ~~said at least one discovered~~ nearby device ~~when an inquiry result includes an indication that at least one nearby device may include a middleware layer, the middleware layer comprising a middleware software for providing application and service discovery;~~  
means for confirming that said ~~at least one~~ nearby device includes the middleware layer software by requesting corresponding information from ~~said at least one~~ nearby device via the wireless short-range communication connection ~~when the inquiry includes the indication that said at least one nearby device may include the middleware layer;~~ and  
means for executing the middleware layer software to perform application and service discovery with said nearby device ~~when said at least one nearby device includes the middleware layer.~~

46. (Previously Presented) The Apparatus of claim 45, wherein the middleware layer includes a service discovery protocol and at least one computer program, each computer program

comprising at least one sequence of operational instructions.

47. (Previously Presented)      The Apparatus of claim 45, further comprising:  
means for executing the middleware layer to launch applications and services when said at  
least one nearby device includes the middleware layer.
48. (Previously Presented)      The Apparatus of claim 45, wherein the means for  
conducting the inquiry further comprises:  
means for sending an inquiry request message; and  
means for receiving an inquiry response message from said at least one nearby device, the  
inquiry response message including the indication.
49. (Previously Presented)      The Apparatus of claim 45, wherein the means for creating  
the wireless short-range connection further comprises:  
means for sending a paging request message directed to said at least one nearby device; and  
means for receiving a paging accept message from said at least one nearby device.
50. (Previously Presented)      The Apparatus of claim 45, wherein the means for  
confirming that said at least one nearby device includes the middleware layer further comprises:  
means for sending a recognition request message to said at least one nearby device; and  
means for receiving a recognition response message from said at least one nearby device,
51. (Previously Presented)      The Apparatus of claim 45, wherein the means for executing  
the middleware layer to perform application and service discovery further comprises:  
means for receiving a notification message from said at least one nearby device, the  
notification message including a local application directory stored in said at least one  
nearby device;  
means for storing an update to a combined application directory, the update based on a  
comparison of the local application directory and the combined application  
directory; and

means for sending an update message to said at least one nearby device, the update message including an update portion of the combined application directory for updating the local application directory stored in said at least one nearby device.

52. (Previously Presented) The Apparatus of claim 51, wherein the means for executing the middleware layer to perform application and service discovery further comprises:

means for launching a local application based on a reference in the combined application directory; and

means for connecting the local application to a counterpart application executing on said at least one nearby device.

53. (Previously Presented) A wireless device, comprising:

a wireless short range transceiver;

a memory device; and

a processor disposed in communication with the memory device, the processor configured to:

~~receive~~ conduct with the transceiver an inquiry ~~request message to discover nearby devices,~~  
determine whether a discovered nearby device provides an indication that it may  
include a middleware software, the middleware software configured for providing  
application and service discovery;

when the discovered nearby device does not provide an indication that it may  
include the middleware software;

disconnect communication session establishment with the discovered nearby  
device;

~~transmit with the transceiver an inquiry response message including when the discovered~~  
nearby device provides an indication that it may include ~~device includes a middleware~~  
~~layer software,~~ said middleware layer comprising a middleware software for providing  
application and service discovery;

create with the transceiver a wireless short-range communication connection

to said ~~at least one~~ the discovered nearby device in response to  
receiving a paging request message from said ~~at least one~~ nearby  
device;

confirm whether said ~~at least one~~ nearby device includes the middleware  
layer software by requesting corresponding information from said ~~at~~  
~~least one~~ nearby device via the wireless short-range communication  
connection; and

when said ~~at least one~~ nearby device includes the middleware layer software:  
execute the middleware layer software to perform application and service  
discovery with said nearby device.